

# Masonite® Flush Door Series

---

## Wood Veneer



Ash\*



Birch



Lauan/Okoume



Oak

Masonite's line of wood veneer doors offer the visual beauty and refinement of natural wood doors. All flush doors are available with hollow or solid core construction and matching bifolds.

## Embossed/Prefinished Hardboard\*



Golden Oak



Tru Oak



Mendocino Oak



Chesapeake



Walnut



Sienna

Masonite's line of Embossed/Prefinished doors provides convenience and versatility. The finish is a precise simulation of authentic wood-grain. Protected with a high quality topcoat, these doors are extremely durable and simple to maintain. They are also available in matching bifolds.

**\*NOTE:** All Embossed/Prefinished colors and Ash veneer are not available in all regions. Colors may vary in actuality to printed pieces. For a door facing sample of available colors, please contact your Masonite Dealer.

## Hardboard



Unprimed



Primed



Primed Textured

Hardboard doors are perfect for small budget renovations. Choose from Unprimed, Primed, or for a subtle wood-grain look, choose Prime Textured. All Hardboard doors have matching bifolds.

## Core Options

The entire Flush Door Series is available in a variety of core options to suit any application. From hollow core to fire-rated, these constructions offer a range of benefits.



**Hollow Core**

Hollow core doors are used where light to medium duty requirements are needed or where lightness of weight is a factor, as in normal residential and office applications. No fire rating is available.



**Particleboard Core**

The stability and durability of particleboard core doors makes them outstanding for general applications. They are available in 1-3/8" or 1-3/4" thickness and a 20-minute fire rating is available in 1-3/4" only.



**Wood Stave Core**

For high use areas where durability is required - as in industrial, commercial and institutional applications. Wood stave cores provide superior vertical stability, screw-holding strength and easy machining for commercial hardware applications. They are available in 1-3/8" or 1-3/4" thickness and with 20-minute fire ratings (1-3/4" only).



**Fire Core**

Mineral core fire doors are available in three ratings: 45-minute, 60-minute and 90-minute — for applications requiring a flush wood door rated to meet specific code requirements (available in 1-3/4" only).

## Matching Bifolds

To keep a consistent look throughout the home or office, consider enhancing the decor with matching Flush Series Bifolds. Bifolds are a great space saving option when there is not enough room for a swinging door. All bifolds come with the necessary hardware for installation.

## Sizes

**Thickness:** 1-3/8" or 1-3/4"

**Bifold Door Widths:** 2-Door Units: 2'0", 2'6", 2'8", 3'0"  
4-Door Units: 4'0", 5'0", 6'0"

**Passage Door Widths:**  
1'0", 1'2", 1'3", 1'4", 1'6", 1'8", 1'10", 2'0",  
2'2", 2'4", 2'6", 2'8", 2'10", 3'0"

**Heights:** 6'6", 6'8", 7'0", 8'0"