



Product Approval

USER: Public User

[Product Approval Menu](#) > [Product or Application Search](#) > [Application List](#) > **Application Detail**

- ▶ COMMUNITY PLANNING
- ▶ HOUSING & COMMUNITY DEVELOPMENT
- ▶ EMERGENCY MANAGEMENT
- ▶ OFFICE OF THE SECRETARY

FL #	FL8692-R1												
Application Type	Affirmation												
Code Version	2007												
Application Status	Approved												
Comments													
Archived													
Product Manufacturer	Masonite International												
Address/Phone/Email	One North Dale Mabry Suite 950 Tampa, FL 33609 (615) 441-4258 sschreiber@masonite.com												
Authorized Signature	Steve Schreiber sschreiber@masonite.com												
Technical Representative													
Address/Phone/Email													
Quality Assurance Representative													
Address/Phone/Email													
Category	Exterior Doors												
Subcategory	Swinging Exterior Door Assemblies												
Compliance Method	Certification Mark or Listing												
Certification Agency	National Accreditation & Management Institute,												
Validated By													
Referenced Standard and Year (of Standard)	<table border="0"> <thead> <tr> <th><u>Standard</u></th> <th><u>Year</u></th> </tr> </thead> <tbody> <tr> <td>ASTM E1300</td> <td>1998</td> </tr> <tr> <td>ASTM E1300</td> <td>2002</td> </tr> <tr> <td>TAS 201</td> <td>1994</td> </tr> <tr> <td>TAS 202</td> <td>1994</td> </tr> <tr> <td>TAS 203</td> <td>1994</td> </tr> </tbody> </table>	<u>Standard</u>	<u>Year</u>	ASTM E1300	1998	ASTM E1300	2002	TAS 201	1994	TAS 202	1994	TAS 203	1994
<u>Standard</u>	<u>Year</u>												
ASTM E1300	1998												
ASTM E1300	2002												
TAS 201	1994												
TAS 202	1994												
TAS 203	1994												
Equivalence of Product Standards													
Certified By													

I affirm that there are no changes in the new Florida Building Code which affect my product(s) and my product(s) are in compliance with the new Florida Building Code.

Documentation from approved Evaluation or Validation Entity Yes No N/A

Product Approval Method Method 1 Option A

Date Submitted 12/24/2008

Date Validated 12/24/2008

Date Pending FBC Approval


Date Approved 01/21/2009

Summary of Products		
FL #	Model, Number or Name	Description
8692.1	Hurricane Belleville Fiberglass Door Unit	6'-8" Opaque I/S and O/S Single Door
Limits of Use Approved for use in HVHZ: Yes Approved for use outside HVHZ: Yes Impact Resistant: Yes Design Pressure: +70.0/-70.0 Other: Evaluated for use in locations adhering to the Florida Building Code including the High Velocity Hurricane Zone, and where pressure requirements as determined by ASCE 7 do not exceed the design pressures listed. 3'-0" x 6'-8" max nominal size. Hurricane protective system is NOT required. See anchor detail DWG-MA-FL0170-07 for additional information.		Certification Agency Certificate FL8692_R1_C_CAC_NI007077.pdf Quality Assurance Contract Expiration Date Installation Instructions FL8692_R1_II_7077_68_Opaque_Anchor_Details.pdf Verified By: National Accreditation & Management Institute, Created by Independent Third Party: Evaluation Reports Created by Independent Third Party:
8692.2	Hurricane Belleville Fiberglass Door Unit	8'-0" Opaque I/S and O/S Single Door
Limits of Use Approved for use in HVHZ: Yes Approved for use outside HVHZ: Yes Impact Resistant: Yes Design Pressure: +70.0/-70.0 Other: Evaluated for use in locations adhering to the Florida Building Code including the High Velocity Hurricane Zone, and where pressure requirements as determined by ASCE 7 do not exceed the design pressures listed. 3'-0" x 8'-0" max nominal size. Hurricane protective system is NOT required. See anchor detail DWG-MA-FL0171-07 for additional information.		Certification Agency Certificate FL8692_R1_C_CAC_NI007077.pdf Quality Assurance Contract Expiration Date Installation Instructions FL8692_R1_II_7077_80_Opaque_Anchor_Details.pdf Verified By: National Accreditation & Management Institute, Created by Independent Third Party: Evaluation Reports Created by Independent Third Party:
8692.3	Hurricane Belleville Fiberglass Door Unit	6'-8" Opaque I/S Single or Double Door w/ or w/o Sidelites
Limits of Use Approved for use in HVHZ: Yes Approved for use outside HVHZ: Yes Impact Resistant: Yes Design Pressure: +50.5/-50.5 Other: Evaluated for use in locations adhering to the Florida Building Code including the High Velocity Hurricane Zone, and where pressure requirements as determined by ASCE 7 do not exceed the design pressures listed. 12'-0" x 6'-8" max nominal size. Hurricane protective system is NOT required. See anchor detail DWG-MA-FL0170-07 for additional information.		Certification Agency Certificate FL8692_R1_C_CAC_NI007077.pdf Quality Assurance Contract Expiration Date Installation Instructions FL8692_R1_II_7077_68_Opaque_Anchor_Details.pdf Verified By: National Accreditation & Management Institute, Created by Independent Third Party: Evaluation Reports Created by Independent Third Party:
8692.4	Hurricane Belleville Fiberglass Door Unit	6'-8" Opaque O/S Single or Double Door w/ or w/o Sidelites
Limits of Use Approved for use in HVHZ: Yes Approved for use outside HVHZ: Yes Impact Resistant: Yes Design Pressure: +55.0/-50.5 Other: Evaluated for use in locations adhering to the Florida Building Code including the High Velocity Hurricane Zone, and where pressure requirements as determined by ASCE 7 do not exceed the design pressures listed. 12'-0" x 6'-8" max nominal size. Hurricane protective system is NOT required. See anchor detail DWG-MA-FL0170-07 for additional information.		Certification Agency Certificate FL8692_R1_C_CAC_NI007077.pdf Quality Assurance Contract Expiration Date Installation Instructions FL8692_R1_II_7077_68_Opaque_Anchor_Details.pdf Verified By: National Accreditation & Management Institute, Created by Independent Third Party: Evaluation Reports Created by Independent Third Party:
8692.5	Hurricane Belleville Fiberglass Door Unit	8'-0" Opaque I/S Single or Double Door w/ or w/o Sidelites
Limits of Use Approved for use in HVHZ: Yes Approved for use outside HVHZ: Yes Impact Resistant: Yes Design Pressure: +50.5/-50.5		Certification Agency Certificate FL8692_R1_C_CAC_NI007077.pdf Quality Assurance Contract Expiration Date Installation Instructions

	<p>Other: Evaluated for use in locations adhering to the Florida Building Code including the High Velocity Hurricane Zone, and where pressure requirements as determined by ASCE 7 do not exceed the design pressures listed. 12'-0" x 8'-0" max nominal size. Hurricane protective system is NOT required. See anchor detail DWG-MA-FL0171-07 for additional information.</p>	<p>FL8692_R1_II_7077_80 Opaque Anchor Details.pdf Verified By: National Accreditation & Management Institute, Created by Independent Third Party: Evaluation Reports Created by Independent Third Party:</p>
<p>8692.6</p> <p>Limits of Use Approved for use in HVHZ: Yes Approved for use outside HVHZ: Yes Impact Resistant: Yes Design Pressure: +55.0/-50.5 Other: Evaluated for use in locations adhering to the Florida Building Code including the High Velocity Hurricane Zone, and where pressure requirements as determined by ASCE 7 do not exceed the design pressures listed. 12'-0" x 8'-0" max nominal size. Hurricane protective system is NOT required. See anchor detail DWG-MA-FL0171-07 for additional information.</p>	<p>Hurricane Belleville Fiberglass Door Unit</p>	<p>8'-0" Opaque O/S Single or Double Door w/ or w/o Sidelites</p> <p>Certification Agency Certificate FL8692_R1_C_CAC_NI007077.pdf Quality Assurance Contract Expiration Date</p> <p>Installation Instructions FL8692_R1_II_7077_80 Opaque Anchor Details.pdf Verified By: National Accreditation & Management Institute, Created by Independent Third Party: Evaluation Reports Created by Independent Third Party:</p>
<p>Limits of Use Approved for use in HVHZ: Yes Approved for use outside HVHZ: Yes Impact Resistant: Yes Design Pressure: +55.0/-55.0 Other: Evaluated for use in locations adhering to the Florida Building Code including the High Velocity Hurricane Zone, and where pressure requirements as determined by ASCE 7 do not exceed the design pressures listed. 12'-0" x 8'-0" max nominal size. Hurricane protective system is NOT required. See anchor detail DWG-MA-FL0172-07 for additional information.</p>	<p>Hurricane Belleville Fiberglass Door Unit</p>	<p>6'-8" Glazed I/S and O/S Single or Double Door w/ or w/o Sidelites</p> <p>Certification Agency Certificate FL8692_R1_C_CAC_NI007077.pdf Quality Assurance Contract Expiration Date</p> <p>Installation Instructions FL8692_R1_II_7077_68 Glazed Anchor Details.pdf Verified By: National Accreditation & Management Institute, Created by Independent Third Party: Evaluation Reports Created by Independent Third Party:</p>
<p>Limits of Use Approved for use in HVHZ: Yes Approved for use outside HVHZ: Yes Impact Resistant: Yes Design Pressure: +43.0/-47.0 Other: Evaluated for use in locations adhering to the Florida Building Code including the High Velocity Hurricane Zone, and where pressure requirements as determined by ASCE 7 do not exceed the design pressures listed. 12'-0" x 8'-0" max nominal size. Hurricane protective system is NOT required. See anchor detail DWG-MA-FL0173-07 for additional information.</p>	<p>Hurricane Belleville Fiberglass Door Unit</p>	<p>8'-0" Glazed I/S Single or Double Door w/ or w/o Sidelites</p> <p>Certification Agency Certificate FL8692_R1_C_CAC_NI007077.pdf Quality Assurance Contract Expiration Date</p> <p>Installation Instructions FL8692_R1_II_7077_80 Glazed Anchor Details.pdf Verified By: National Accreditation & Management Institute, Created by Independent Third Party: Evaluation Reports Created by Independent Third Party:</p>
<p>Limits of Use Approved for use in HVHZ: Yes Approved for use outside HVHZ: Yes Impact Resistant: Yes Design Pressure: +47.0/-45.0 Other: Evaluated for use in locations adhering to the Florida Building Code including the High Velocity Hurricane Zone, and where pressure requirements as determined by ASCE 7 do not exceed the design pressures listed. 12'-0" x 8'-0" max nominal size. Hurricane protective system is NOT required. See anchor detail DWG-MA-FL0173-07 for additional information.</p>	<p>Hurricane Belleville Fiberglass Door Unit</p>	<p>8'-0" Glazed O/S Single or Double Door w/ or w/o Sidelites</p> <p>Certification Agency Certificate FL8692_R1_C_CAC_NI007077.pdf Quality Assurance Contract Expiration Date</p> <p>Installation Instructions FL8692_R1_II_7077_80 Glazed Anchor Details.pdf Verified By: National Accreditation & Management Institute, Created by Independent Third Party: Evaluation Reports Created by Independent Third Party:</p>
<p>Limits of Use Approved for use in HVHZ: Yes Approved for use outside HVHZ: Yes Impact Resistant: Yes Design Pressure: +55.0/-55.0 Other: Evaluated for use in locations adhering to the Florida Building Code including the High Velocity Hurricane Zone, and where pressure requirements as determined by ASCE 7 do not exceed the design pressures listed. 12'-0" x 8'-0" max nominal size. Hurricane protective system is NOT required. See anchor detail DWG-MA-FL0173-07 for additional information.</p>	<p>Hurricane Belleville Fiberglass Door Unit</p>	<p>8'-0" Glazed I/S and O/S Single or Double Door w/ or w/o Sidelites (with surface bolts)</p> <p>Certification Agency Certificate FL8692_R1_C_CAC_NI007077.pdf Quality Assurance Contract Expiration Date</p> <p>Installation Instructions FL8692_R1_II_7077_80 Glazed Anchor Details.pdf Verified By: National Accreditation & Management Institute, Created by Independent Third Party: Evaluation Reports Created by Independent Third Party:</p>

[Back](#)

[Next](#)



(850) 487-1824, Fax (850) 414-8436

© 2000-2005 The State of Florida. All rights reserved. [Copyright and Disclaimer](#)

Product Approval Accepts:

