





Performance based on assembled door units utilizing Masonite sidelite panels,  
NFRC default sill, and default wood frame.

<b>ENERGY PERFORMANCE RATING</b>				
	<b>U-Factor/Solar Heat Gain Coefficient (SHGC)</b>			
<b>Product description*</b>	 <b>1/4 Lite</b>	 <b>1/2 Lite</b>	 <b>3/4 Lite</b>	 <b>Full Lite</b>
Wood-edge Steel with 1/2" IG	0.18 / 0.03	0.31 / 0.21	0.39 / 0.31	0.43 / 0.38
Wood-edge Steel with 1/2" IG external grid	0.18 / 0.03	0.31 / 0.19	0.39 / 0.28	0.43 / 0.34
Wood-edge Steel with 1" IG	0.18 / 0.03	0.30 / 0.21	0.36 / 0.31	0.41 / 0.38
Wood-edge Steel with 1" IG internal grid	0.18 / 0.03	0.30 / 0.19	0.36 / 0.28	0.41 / 0.34
Wood-edge Steel with 1" Low-E IG	0.17 / 0.03	0.27 / 0.20	0.32 / 0.30	0.35 / 0.37
Wood-edge Steel with 1" Decorative IG	0.17 / 0.04	0.26 / 0.17	0.31 / 0.25	0.34 / 0.31

ATI report # 69857.01-116-45r1

Energy performance values have been established in accordance with the International Energy Conservation Code (**IECC**); U-factors determined in accordance to NFRC 100 & SHGC values determined in accordance with NFRC 200. See prescriptive performance criteria for ENERGY STAR and/or IECC climate zones as well as local building codes.

\* Based on 16" max. sidelite unit width.