



MASONITE QUALIFYING PRODUCTS FOR 2009 & 2010 TAX CREDITS
NFRC Certified Assembly Utilizing Specialty™ Insulated Glass

DOORS (U Factor / SHGC)			Fiberglass Door Systems						Wood-edge Steel Door Systems						Metal-edge Steel Door Systems					
Glass Code	Glass Description	NFRC Classification	Clear 1/2" IG	Clear 1/2" IG w/Grids	Clear 1" IG	1" LowE IG Surface #2	1" LowE IG Surface #2 w/Grids	Decorative w/ Caming	Clear 1/2" IG	Clear 1/2" IG w/Grids	Clear 1" IG	1" LowE IG Surface #2	1" LowE IG Surface #2 w/Grids	Decorative w/ Caming	Clear 1/2" IG	Clear 1/2" IG w/Grids	Clear 1" IG	1" LowE IG Surface #2	1" LowE IG Surface #2 w/Grids	Decorative w/ Caming
----	No Glass	Opaque	←----- 0.14 / 0.01 ----->						←----- 0.14 / 0.01 ----->						←----- 0.16 / 0.01 ----->					
136	7.5" x 18.5" Rectangle	Quarter Lite	.22 / .12	.22 / .12	.21 / .12	.20 / .10	.20 / .10	.19 / .09	.17 / .03	.17 / .03	.17 / .03	.20 / .10	.20 / .10	.17 / .03	.21 / .06	.21 / .06	.20 / .06	.20 / .05	.20 / .05	.19 / .05
135	22" x 10" Half Circle	Quarter Lite	.22 / .12	.22 / .12	.21 / .12	.20 / .10	.20 / .10	.19 / .09	.17 / .03	.17 / .03	.17 / .03	.20 / .10	.20 / .10	.17 / .03	.21 / .06	.21 / .06	.20 / .06	.20 / .05	.20 / .05	.19 / .05
137	22" x 10" Camber Top	Quarter Lite	.22 / .12	.22 / .12	.21 / .12	.20 / .10	.20 / .10	.19 / .09	.17 / .03	.17 / .03	.17 / .03	.20 / .10	.20 / .10	.17 / .03	.21 / .06	.21 / .06	.20 / .06	.20 / .05	.20 / .05	.19 / .05
228	22" x 10" Rectangle	Quarter Lite	.22 / .12	.22 / .12	.21 / .12	.20 / .10	.20 / .10	.19 / .09	.17 / .03	.17 / .03	.17 / .03	.20 / .10	.20 / .10	.17 / .03	.21 / .06	.21 / .06	.20 / .06	.20 / .05	.20 / .05	.19 / .05
203	8" x 42" Round Top	Quarter Lite	.22 / .12	.22 / .12	.21 / .12	.20 / .10	.20 / .10	.19 / .09	.17 / .03	.17 / .03	.17 / .03	.20 / .10	.20 / .10	.17 / .03	.21 / .06	.21 / .06	.20 / .06	.20 / .05	.20 / .05	.19 / .05
201	8" x 58" Round Top	Half Lite	.30 / .24	.30 / .23	.29 / .24	.25 / .20	.25 / .19	.25 / .17	.29 / .19	.29 / .17	.27 / .19	.25 / .20	.25 / .19	.24 / .16	.33 / .25	.33 / .23	.31 / .25	.28 / .21	.28 / .19	.27 / .22
304	16" x 40" Oval	Half Lite	.30 / .24	.30 / .23	.29 / .24	.25 / .20	.25 / .19	.25 / .17	.29 / .19	.29 / .17	.27 / .19	.25 / .20	.25 / .19	.24 / .16	.33 / .25	.33 / .23	.31 / .25	.28 / .21	.28 / .19	.27 / .22
306	15" x 55" Oval	Half Lite	.30 / .24	.30 / .23	.29 / .24	.25 / .20	.25 / .19	.25 / .17	.29 / .19	.29 / .17	.27 / .19	.25 / .20	.25 / .19	.24 / .16	.33 / .25	.33 / .23	.31 / .25	.28 / .21	.28 / .19	.27 / .22
105	22" x 36" Round Top	Half Lite	.30 / .24	.30 / .23	.29 / .24	.25 / .20	.25 / .19	.25 / .17	.29 / .19	.29 / .17	.27 / .19	.25 / .20	.25 / .19	.24 / .16	.33 / .25	.33 / .23	.31 / .25	.28 / .21	.28 / .19	.27 / .22
106	22" x 36" Rectangle	Half Lite	.30 / .24	.30 / .23	.29 / .24	.25 / .20	.25 / .19	.25 / .17	.29 / .19	.29 / .17	.27 / .19	.25 / .20	.25 / .19	.24 / .16	.33 / .25	.33 / .23	.31 / .25	.28 / .21	.28 / .19	.27 / .22
107	22" x 37" Camber Top	Half Lite	.30 / .24	.30 / .23	.29 / .24	.25 / .20	.25 / .19	.25 / .17	.29 / .19	.29 / .17	.27 / .19	.25 / .20	.25 / .19	.24 / .16	.33 / .25	.33 / .23	.31 / .25	.28 / .21	.28 / .19	.27 / .22
300	20" x 57" Oval	Half Lite	.30 / .24	.30 / .23	.29 / .24	.25 / .20	.25 / .19	.25 / .17	.29 / .19	.29 / .17	.27 / .19	.25 / .20	.25 / .19	.24 / .16	.33 / .25	.33 / .23	.31 / .25	.28 / .21	.28 / .19	.27 / .22
410	22" x 47" S-Top	3/4 Lite	.33 / .29	.33 / .27	.31 / .29	.27 / .24	.27 / .23	.26 / .20	.35 / .29	.35 / .25	.33 / .29	.27 / .24	.27 / .23	.28 / .24	.39 / .34	.39 / .31	.37 / .34	.31 / .29	.31 / .26	.30 / .31
404	22" x 48" Rectangle	3/4 Lite	.33 / .29	.33 / .27	.31 / .29	.27 / .24	.27 / .23	.26 / .20	.35 / .29	.35 / .25	.33 / .29	.27 / .24	.27 / .23	.28 / .24	.39 / .34	.39 / .31	.37 / .34	.31 / .29	.31 / .26	.30 / .31
120	20" x 64" Rectangle	Full Lite	.38 / .36	.38 / .34	.35 / .37	.30 / .30	.30 / .29	.29 / .25	.39 / .35	.39 / .31	.36 / .35	.30 / .30	.30 / .29	.30 / .29	.44 / .43	.44 / .38	.41 / .43	.34 / .36	.34 / .32	.33 / .39
109	22" x 64" Round Top	Full Lite	.38 / .36	.38 / .34	.35 / .37	.30 / .30	.30 / .29	.29 / .25	.39 / .35	.39 / .31	.36 / .35	.30 / .30	.30 / .29	.30 / .29	.44 / .43	.44 / .38	.41 / .43	.34 / .36	.34 / .32	.33 / .39
122	22" x 64" Rectangle	Full Lite	.38 / .36	.38 / .34	.35 / .37	.30 / .30	.30 / .29	.29 / .25	.39 / .35	.39 / .31	.36 / .35	.30 / .30	.30 / .29	.30 / .29	.44 / .43	.44 / .38	.41 / .43	.34 / .36	.34 / .32	.33 / .39
810	22" x 80" Rectangle	Full Lite	.38 / .36	.38 / .34	.35 / .37	.30 / .30	.30 / .29	.29 / .25	.39 / .35	.39 / .31	.36 / .35	.30 / .30	.30 / .29	.30 / .29	.44 / .43	.44 / .38	.41 / .43	.34 / .36	.34 / .32	.33 / .39
Steel frame add .08 U value to all configurations									Steel frame add .07 U value to all configurations						Steel frame add .10 U value to all configurations					

SIDELITES (U Factor / SHGC)			Fiberglass Sidelites						Wood-edge Steel Sidelites						Performance based on assembled door using Masonite standard panels , Specialty Glass, NFRC default sill, and default wood frame. Energy Performance values have been established in accordance with the International Energy Conservation Code (IECC); U-factors determined in accordance to NFRC 100 and SHGC values determined in accordance with NFRC 200. See prescriptive performance criteria for Energy Star and or IECC climate zones as well as local building codes. This is a general guideline, the NFRC performance label attached to the product, is the official performance document.
Glass Code	Glass Description	NFRC Classification	Clear 1/2" IG	Clear 1/2" IG w/Grids	Clear 1" IG	1" LowE IG Surface #2	1" LowE IG Surface #2 w/Grids	Decorative w/ Caming	Clear 1/2" IG	Clear 1/2" IG w/Grids	Clear 1" IG	1" LowE IG Surface #2	1" LowE IG Surface #2 w/Grids	Decorative w/ Caming	
		Quarter Lite	.20 / .04	.20 / .04	.20 / .04	.20 / .03	.20 / .04	.19 / .04	.18 / .03	.18 / .03	.18 / .03	.17 / .03	.17 / .03	.17 / .04	
129	8" x 36" Rectangle	Half Lite	.28 / .13	.28 / .13	.28 / .13	.26 / .11	.26 / .11	.25 / .12	.31 / .21	.31 / .19	.30 / .21	.27 / .18	.27 / .16	.26 / .17	
200	8" x 36" Round Top	Half Lite	.28 / .13	.28 / .13	.28 / .13	.26 / .11	.26 / .11	.25 / .12	.31 / .21	.31 / .19	.30 / .21	.27 / .18	.27 / .16	.26 / .17	
450	8" x 48" Rectangle	3/4 Lite	.32 / .18	.32 / .17	.31 / .18	.29 / .15	.29 / .14	.27 / .17	.39 / .31	.39 / .28	.36 / .31	.32 / .27	.32 / .24	.31 / .25	
152	7" x 64" Rectangle	Full Lite	.35 / .23	.35 / .21	.35 / .23	.33 / .19	.33 / .18	.30 / .21	.43 / .38	.43 / .34	.41 / .38	.35 / .33	.35 / .29	.34 / .31	
149	8" x 64" Round Top	Full Lite	.37 / .23	.37 / .21	.36 / .23	.33 / .19	.33 / .18	.30 / .21	.43 / .38	.43 / .34	.41 / .38	.35 / .33	.35 / .29	.34 / .31	
151	8" x 64" Rectangle	Full Lite	.37 / .23	.37 / .21	.36 / .23	.33 / .19	.33 / .18	.30 / .21	.43 / .38	.43 / .34	.41 / .38	.35 / .33	.35 / .29	.34 / .31	
852	8" x 80" Rectangle	Full Lite	.37 / .23	.37 / .21	.36 / .23	.33 / .19	.33 / .18	.30 / .21	.43 / .38	.43 / .34	.41 / .38	.35 / .33	.35 / .29	.34 / .31	

 = Qualified Door or Sidelite Unit
 = Multiple Constructions exist, for tax credit eligible construction please specify "FCO" when ordering

Instructions to Receive Tax Credit

1. Place into service any NFRC certified window, patio door, or entry door with a U-factor and Solar Heat Gain Coefficient of .30 or below between January 1, 2009 and December 31, 2010
2. Save your receipt for each door or sidelite and their NFRC performance label with your tax documents.
3. Claim you tax credit on your Federal filing for the 2009 or 2010 tax year.